

# ARTEX®

First for finishes

## Site Finish



Site Finish is specially formulated for application to new plasterboard. It is suitable for both preparation and texturing work. The mix is ideal for creating the quality finish needed on site. Available in 25kg bags.

### Product Benefits

1. Site Finish is specially designed for new site work as it dries white, eliminating the need for painting.
2. Site Finish offers a unique low odour formulation and mixes easily with cold water.
3. It has an enhanced wet-edge time to achieve better glide, improving the consistency of the pattern.

### Mixing

Pour the required amount of cold water (above 5°C) into a clean bucket. Use approximately 0.5 litres for every 1kg of Site Finish. Add the Site Finish to the water slowly and mix to a thick creamy consistency with an Artex Mixing Tool. Leave to stand for 10 - 15 minutes, then remix to a smooth paste.

Adjust as required for filling joints and caulking.

For texturing work gradually dilute with cold water and mix to the required consistency, but avoid over thinning.

For rich textures add approximately 100ml of clean water for every 1kg of Site Finish and mix to a creamy consistency.

For light textures add approximately 200ml of clean water for every 1kg of Site Finish.

### Coverage

Coverage depends on the background type, method of use and depth of texture. 25kg would normally cover:

- Jointing and Texturing 15-25m<sup>2</sup>
- Light textures up to 50m<sup>2</sup>
- Rich textures up to 20m<sup>2</sup>

### Technical Advice Service

Artex Limited has experienced representatives available to provide specifiers and product users with skilled assistance in their choice and use of Artex products, simply call 0800 032 6345.

Training courses are available to provide contractors with essential texturing skills. For more information please contact the Product Training Centre on 0870 240 6040

### Quality Assurance

Artex Limited is a quality assured company registered with BSI Certificate number FM 12791.



Artex Limited  
Head Office,  
Pasture Lane,  
Ruddington,  
Nottinghamshire,  
NG11 6AE  
Tel: +44 (0) 800 032 6345 Fax: +44 (0) 115 945 6041  
[www.artexltd.com](http://www.artexltd.com)

The Artex logo is a registered trademark of BPB United Kingdom Limited part of the Saint-Gobain Group

# ARTEX®

First for finishes

## Ceiling Finish



Ceiling Finish has been specially formulated for use on refurbishment projects, with particular consideration given to the changing trends in modern interior design. Available in 25kg bags.

### Product Benefits

1. Ceiling Finish has a revolutionary low odour formulation making it ideal for use on refurbishment projects.
2. Ceiling Finish has excellent build properties and is highly suitable for re-texturing work.
3. It is easily mixed with cold water.

### Mixing

Pour the required amount of cold water (above 5°C) into a clean bucket. Use approximately 0.5 litres for every 1kg of Ceiling Finish. Add the Ceiling Finish to the water slowly and mix to a thick creamy consistency with an Artex Mixing Tool. Leave to stand for 10 - 15 minutes, then remix to a smooth paste.

Adjust as required for filling joints and caulking. For texturing work gradually dilute with cold water and mix to the required consistency, but avoid over thinning.

For rich textures add approximately 100ml of clean water for every 1kg of Ceiling Finish and mix to a creamy consistency. For light textures add approximately 200ml of clean water for every 1kg of Ceiling Finish.

*Do not mix more than can be used within 3 hours*

If the mix begins to set before it can be applied, discard the material, clean the container and tools thoroughly and mix a fresh batch.

### Coverage

Coverage depends on the background type, method of use and depth of texture. 25kg would normally cover:

- Jointing and Texturing 15-25m<sup>2</sup>
- Light textures up to 50m<sup>2</sup>
- Rich textures up to 20m<sup>2</sup>

### Technical Advice Service

Artex Limited has experienced representatives available to provide specifiers and product users with skilled assistance in their choice and use of Artex products, simply call 0800 032 6345.

Training courses are available to provide contractors with essential texturing skills. For more information please contact the Product Training Centre on 0870 240 6040

### Quality Assurance

Artex Limited is a quality assured company registered with BSI Certificate number FM 12791.



Artex Limited  
Head Office,  
Pasture Lane,  
Ruddington,  
Nottinghamshire,  
NG11 6AE  
Tel: +44 (0) 800 032 6345 Fax: +44 (0) 115 945 6041  
[www.artexltd.com](http://www.artexltd.com)

The Artex logo is a registered trademark of BPB United Kingdom Limited part of the Saint-Gobain Group