



DECLARATION OF PERFORMANCE

1. Unique identification code of the product-type :

Roofing Felt Standard Green Mineral Finish

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4) :

Blue Hawk Standard Green Mineral Finish Felt

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer :

An economy shed felt for use on non-habitable garden outbuildings and animal shelters. A recycled rag fibre based oxidised bitumen roofing membrane with a fine sand upper surface.

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5) :

**Artex Limited,
Registered in England 4140239
Pasture Lane, Ruddington, Nottingham, Nottinghamshire, NG11 6AE
Tel : 0800 032 6345**

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

N/A

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

2+

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

EN13707: 2004+A2: 2009

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

N/A

9. Declared performance:

The characteristics in the table below apply to all products mentioned in 2 above.

Essential Characteristics	Performance	Harmonised technical specification
Roll length*	5m / 10m	BS EN 1848-1
Roll width**	1m	BS EN 1848-1
Weight***	10kg / 20kg	BS EN 1849-1
Watertightness	Pass	BS EN 1928 method a.
Tensile strength****		BS EN 12311-1
Longitudinal	365 N/50mm	
Transverse	225 N/50mm	
Elongation at maximum load		BS EN 12311-1
Longitudinal	2%	
Transverse	3%	
Resistance to tearing****		BS EN 12310-1
Longitudinal	135 N	
Transverse	125 N	
Straightness	Pass	BS EN1848-1
Visible defects	Pass	BS EN1850-1
Artificial ageing behaviour		
Exposure to elevated temperature	NPD	BS EN1296
Exposure to UV radiation, elevated temperature and water	NPD	BS EN 1297

*tolerance of ≥ 150 mm **tolerance of $\pm 1.5\%$ ***tolerance of $\pm 7.5\%$ ****tolerance of $\pm 15\%$

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Certified in accordance with:
Environmental Management System ISO 14001:2004,
Quality Management System ISO 9001:2008.

Signed for and on behalf of the manufacturer by:

Carl Gardner, Retail Business Unit Director


.....
Signature

23/8/2013 *RIDDINGTON*
.....
Place and date of issue