



DECLARATION OF PERFORMANCE

1. Unique identification code of the product-type :

Roofing Felt Heavy Grade Green Mineral Finish

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4) :

Blue Hawk Heavy Duty Green Mineral Felt

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer :

A heavy grade traditional green mineral felt for use on larger garden outbuildings, also as a top sheet for garages and smaller domestic extensions when used as part of a multi-layer roof system. A recycled rag fibre based oxidised bitumen roofing membrane with a coarse green slate granule upper surface to aid UV protection.

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5) :

**Artex Limited,
Registered in England 4140239
Pasture Lane, Ruddington, Nottingham, Nottinghamshire, NG11 6AE
Tel : 0800 032 6345**

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

N/A

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

2+

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

EN13707: 2004+A2: 2009

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

BBA

9. Declared performance:

The characteristics in the table below apply to all products mentioned in 2 above.

Essential Characteristics	Performance	Harmonised technical specification
Roll length*	10m	BS EN 1848-1
Roll width**	1m	BS EN 1848-1
Weight***	29kg	BS EN 1849-1
Watertightness	Pass	BS EN 1928 method a.
Tensile strength****		BS EN 12311-1
Longitudinal	365 N/50mm	
Transverse	225 N/50mm	
Elongation at maximum load		BS EN 12311-1
Longitudinal	2%	
Transverse	3%	
Resistance to tearing****		BS EN 12310-1
Longitudinal	135 N	
Transverse	125 N	
Straightness	Pass	BS EN1848-1
Visible defects	Pass	BS EN1850-1
Artificial ageing behaviour		
Exposure to elevated temperature	NPD	BS EN1296
Exposure to UV radiation, elevated temperature and water	NPD	BS EN 1297

*tolerance of ≥ 150 mm **tolerance of $\pm 1.5\%$ ***tolerance of $\pm 7.5\%$ ****tolerance of $\pm 15\%$

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Certified in accordance with:
Environmental Management System ISO 14001:2004,
Quality Management System ISO 9001:2008.

Signed for and on behalf of the manufacturer by:

Carl Gardner, Retail Business Unit Director


.....
Signature

.....
RIDDINGTON, 28/8/2015
Place and date of issue