
































Plasterboard Selector Guide

British Gypsum plasterboards are the ultimate lining for today's buildings, providing high levels of fire, acoustic, thermal, moisture, impact resistance and fixing capability to create modern internal environments that offer comfort and safety for occupants.

	Standard board	
		
	Gyproc WallBoard	Gyproc Plank
	Used in drylining, masonry, timber frame and metal frame (walls, partitions and ceilings)	Located as an inner layer or for improving acoustics
Performance	-	-
Thickness (mm)	9.5, 12.5, 15	19.0
Width (mm)	900 - 1200	600
Length (mm)	1800 - 3600	2400
Weight per board (kg) ¹	11.6 - 38.4	23.2
Edge profile	TE SE	TE SE
Standards and certification	BS EN 520 - Type A	BS EN 520 - Type A
Finishing	Thistle MultiFinish, Thistle BoardFinish or ThistlePro PureFinish 	Thistle MultiFinish, Thistle BoardFinish or ThistlePro PureFinish 
Variants	Gyproc HandiBoard Gyproc WallBoard Gyproc WallBoard DUPLEX Gyproc WallBoard 4TE Gyproc WallBoard TEN	-

Performance board						
						
Gyproc Habito	Gyproc Moisture Resistant	Gyproc FireLine	Gyproc CoreBoard	Gyproc SoundBloc	Gyproc DuraLine	Gyproc ThermaLine
The new standard for residential, new build and RMI with inbuilt fixing capability	Moisture resistant board designed for use in areas such as kitchens and bathrooms	Increased fire resistance for garages, fire escape routes or separating floors in flats	Used to protect all forms of shafts and ducts in conventional buildings	Enhanced sound insulation performance for partitions and floors	An increased robustness for high traffic areas such as hallways, stairs and landing areas	Creating an advanced level of thermal insulation meeting required U-Values
						
12.5	12.5, 15	12.5, 15	19	12.5, 15	15	22 - 93
900 - 1200	1200	900 - 1200	598	1200	1200	1200
2400 - 3000	2400 - 3000	1800 - 3000	3000	2400 - 3000	2400 - 3000	2400
35.6 - 44.6	25.7 - 32.3	16.9 - 47.0	30.1	34.0 - 52.3	42.7 - 53.5	19.8 - 32.0
TE	TE SE	TE SE	SE	TE	TE	TE
BS EN 520 - Type A	BS EN 520 - Type A, HI	BS EN 520 - Type F	BS EN 520 - Type D, F, HI	BS EN 520 - Type D	BS EN 520 - Type D, F, I, R	EN 13950
Thistle MultiFinish, Thistle BoardFinish (timber frame, Dot & Dab or 900 metal systems only) or ThistlePro PureFinish 	Thistle MultiFinish, Thistle BoardFinish (pre-treated with Thistle Bond-It) or ThistlePro PureFinish 	Thistle MultiFinish, Thistle BoardFinish or ThistlePro PureFinish 	Not recommended	Thistle MultiFinish, Thistle BoardFinish or ThistlePro PureFinish 	Thistle MultiFinish, Thistle BoardFinish or ThistlePro PureFinish 	Thistle MultiFinish, Thistle BoardFinish or ThistlePro PureFinish 
-	-	Gyproc FireLine MR Gyproc FireLine DUPLEX	-	Gyproc SoundBloc MR Gyproc SoundBloc F Gyproc SoundBloc RAPID Gyproc SoundBloc RAPID MR	Gyproc DuraLine MR	Gyproc ThermaLine BASIC Gyproc ThermaLine PLUS Gyproc ThermaLine PIR Gyproc ThermaLine PIR MR Gyproc ThermaLine SUPER

Performance key

-  Enhanced sound performance
-  Enhanced moisture performance
- TE** Tapered edge board
-  Enhanced fire performance
-  Enhanced thermal performance
- SE** Square edge board
-  Enhanced robust performance
-  Enhanced fixing performance
-  **ACTIVair** technology

¹ For loading purposes only.

Why not use our boards in one of the many lining systems British Gypsum has to offer?

All of our systems are covered by the SpecSure® lifetime system warranty when using genuine British Gypsum and Saint-Gobain Isover products. For more information visit british-gypsum.com