

Speed up patch repairs with **Thistle Bonding 60**. It consistently sets in 60 minutes taking out the guesswork and reducing the risk of cracking and shrinkage.

**“It mixes up the same as Thistle Bonding Coat but is smoother off the trowel and sets more evenly.**

**It gives a professional solution to an issue we’ve all faced many times, without guesswork or compromise.”**



**Gary Blackburn**  
Thistle Plaster Demonstrator for the East Midlands region.  
**@GaryB\_BG**

Find out what our demonstrators think at [british-gypsum.com](http://british-gypsum.com)



(10kg/5kg bags)

### Want a rapid, sandable finish too?

From start to finish in less than 2 hours, try Gyproc Easi-Fill 60 or Easi-Fill 20 as a finish coat once Thistle Bonding 60 has been used for patching.

## Thistle Bonding 60

New quick-setting repair and patching plaster for a professional quality finish with reduced risk of shrinkage and cracking



Available in **25kg** and **12.5kg** bags and a **10kg** powder in tub option for less waste and easy storage.



British Gypsum  
Head Office  
East Leake, Loughborough  
Leicestershire LE12 6HX  
T: + 44(0)115 945 1000

July 2017 BG-TBL-04

[british-gypsum.com](http://british-gypsum.com)

@britishgypsum

[www.linkedin.com/company/british-gypsum](https://www.linkedin.com/company/british-gypsum)





# 60 Minutes Flat

Wall repair can be time consuming and awkward, especially where new cabling or pipework has been installed. Waiting for the product to set can take hours.

Using tricks of the trade to save time can result in shrinkage, cracking and unpredictable set times.

With Thistle Bonding 60 there's no more waiting around. It provides a consistent 60 minute set time, meaning jobs are completed faster while never compromising on quality.

## FAQs.

### What is the setting time?



Like other Thistle plasters you will see set-time performance changes based on the suction of the background and the method of control you apply.

### Which backgrounds will it work on?

We recommend using Thistle Bonding 60 on medium to lower suction backgrounds, in renovation and refurbishment applications. All backgrounds need to be clean, sound and free from dust.

#### No pre-treatment is needed for;

- Medium-density blocks
- Engineering bricks
- Metal lathing

#### We recommend pre-treatment with;

- Dense blocks
- Plasterboard
- Cast-in-situ and pre-cast concrete
- Painted and tiled surfaces
- Ceilings

### What about backgrounds not listed here?

We suggest that you try a small test area before the larger job.

For extremely high suction backgrounds, suction control is needed, e.g. with Thistle Bond-It or PVA.

When suction is high but not extreme, suction control may still be advisable, but is not usually necessary.

### How does it differ from standard Thistle BondingCoat?

Aside from the reduced working time (45min) and setting time (60min), Thistle Bonding 60 has a different smell and feel to it compared to other Thistle undercoat plasters.

The specially formulated additives give the plaster a unique texture to work with, often compared to older formulation products in how it feels to use.

You may need to make some changes to site practice. Thistle Bonding 60 will set on the edges of tools left too long before cleaning down. Also, we strongly recommend using clean water and a clean bucket for mixing in to avoid inconsistent performance.

### What are the product benefits of Thistle Bonding 60?

- Removes the need for tricks of the trade, giving a consistent professional set every time
- Suitable for use on a wide range of backgrounds
- Thistle Bonding 60 cuts out the dead-time in your small patching jobs
- Less risk of cracking or shrinkage
- Saves time during the day, get home quicker
- Excellent workability on medium and low suction backgrounds
- Easy to mix and easy to use



For more information, product specification sheets, how-to guides and videos visit [british-gypsum.com](http://british-gypsum.com)